



Model Name	WebOP-3070T/3100T/3150T	SPC-1840WP	FPM-7181W/7211W	TPC-1840WP	TPC-2140WP	
CPU	RISC 32 bits ARM® Cortex™-A8 600MHz	AMD® dual core 1.65GHz	-	AMD® dual core 1.65GHz	AMD® dual core 1.65GHz	
Memory	256MB on-board DDR2	4GB SO-DIMM DDR3	-	4GB SO-DIMM DDR3	4GB SO-DIMM DDR3	
Display	Display Type	WXGA TFT LED LCD	WXGA / Full HD / TFT LED LCD	WXGA TFT LED LCD	Full HD TFT LED LCD	
	Display Size	7" / 10.1" / 15"	18.5"	18.5" / 21.5"	18.5"	21.5"
	Max. Resolution	800 x 480 / 1024 x 600 / 1024 x 768	1366 x 768	1366 x 768 / 1920 x 1080	1366 x 768	1920 x 1080
	Max. Colors	262 K	16.2 M	16.2 M / 16.7M	16.2 M	16.7 M
	Luminance cd/m ²	500 / 550 / 400	300	300 / 300	300	300
	Viewing Angle (H/V°)	140/120 / 140/110 / 160/140	170/160	170/160 / 178/178	170/160	178/178
Backlight MTBF (hrs)	50000	50000	50000	50000	50000	
Video Port	-	-	VGA & DVI-D port	HDMI port x 1	HDMI port x 1	
Touchscreen	5 wire analog resistive	Projected capacitive touch	5 wire analog resistive	Projected capacitive touch	Projected capacitive touch	
Network (LAN)	10/100Base-T x 1	10/100/1000Base-T x 2, M12 connector	-	10/100/1000Base-T x 2	10/100/1000Base-T x 2	
I/O Ports	COM1: RS-232/422/485 (DB9) COM2: RS-422/485 (TB 4pin) COM3: RS-485 (TB 2pin) CAN: TB 2pin USB 2.0 x 1(Host) USB 1.1 x 1(Client) Mic in x 1, Line out x 1	RS-232 x 1, M12 connector USB 2.0 x 1, M12 connector 24 V _{oc} connector, M12 connector	RS-232 and USB interface for touch screen	RS-232 x 3 RS-422 / 485 x 1 USB 2.0 x 2(Host) Mic in x 1, Line out x 1	RS-232 x 3 RS-422 / 485 x 1 USB 2.0 x 2(Host) Mic in x 1, Line out x 1	
HDD (Optional)	-	2.5" SATA HDD	-	2.5" SATA HDD	2.5" SATA HDD	
Intelligent Keys	-	Quick access through built-in front bezel function and home key button	-	Quick access through built-in front bezel function and home key button	Quick access through built-in front bezel function and home key button	
CompactFlash Slots	-	-	-	CFast slot x 1	CFast slot x 1	
Expansion Slots	Micro-SD slot x 1	Full-sized mini PCI-E x 1	-	Full-sized mini PCI-E x 1	Full-sized mini PCI-E x 1	
Power Input Voltage	24V _{oc} ± 10%	24 V _{oc} connector, M12 connector	Phoenix Jack: 24 V _{oc} input DC Jack 12 V _{oc} @ 4.75 A output by External power adapter	18 ~ 32 V _{oc}	18 ~ 32 V _{oc}	
Ingress Protection (Front Panel)	Front panel NEMA4/IP66 compliant	All around NEMA4/IP65	Front panel NEMA4/IP65 compliant	Front panel NEMA4/IP65 compliant	Front panel NEMA4/IP65 compliant	
Enclosure	Front panel: Die-cast aluminum alloy	Front bezel: Die-cast aluminum alloy Back housing: Die-cast aluminum alloy	Front panel: Die-cast magnesium alloy Rear cover: SECC	Front bezel: Die-cast magnesium alloy Back housing: PC/ABS Resin	Front bezel: Die-cast magnesium alloy Back housing: PC/ABS Resin	
Mounting	Panel, VESA arm	Desktop, wall, VESA arm	Desktop, wall or panel mount	Desktop, wall or panel mount	Desktop, wall or panel mount	
Operating Temperature	-20 ~ 60°C (-4 ~ 140°F)	0 ~ 50°C (32 ~ 122°F)	0 ~ 50°C (32 ~ 122°F)	0 ~ 50°C (32 ~ 122°F)	0 ~ 50°C (32 ~ 122°F)	
Storage Temperature	-30 ~ 70°C (-22 ~ 158°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	
Dimension	203.4 x 150 x 43.7 mm (8.01" x 5.91" x 1.72")	488 x 309 x 65 mm (19.2" x 21.2" x 2.6")	488 x 309 x 45.7 mm (19.2" x 21.2" x 1.8")	488.1 x 309.1 x 56.7 mm (19.2" x 12.2" x 2.2")	580.7 x 355.3 x 56.7 mm (22.8" x 14" x 2.2")	
	271.5 x 213.5 x 43.2 mm (10.69" x 8.41" x 1.7")		561 x 356 x 45.7 mm (22.1" x 14" x 1.8")			
	386 x 310 x 46.8 mm (15.20" x 12.2" x 1.84")					
Weight	1 kg (2.20 lbs)	7 kg (15.4 lbs)	6 kg (13.2 lbs)	7 kg (15.44 lbs)	8 kg (17.64 lbs)	
	1.2 kg (2.65 lbs)		8 kg (17.6 lbs)			
	3 kg (6.61 lbs)					
Certification	BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL	BSMI, CCC, CE, FCC Class A, UL	
Operating System	Microsoft® WinCE 6.0	Microsoft® Win8/WES7P /XP/WES2009/WinCE 6.0 /Linux	Microsoft® Win8/WES7P /XP/WES2009/WinCE 6.0 /Linux	Microsoft® Win8/WES7P /XP/WES2009/WinCE 6.0 /Linux	Microsoft® Win8/WES7P /XP/WES2009/WinCE 6.0 /Linux	

Regional Service & Customization Centers

China	Taiwan	Netherlands	Poland	USA/ Canada
Kunshan 86-512-5777-5666	Taipei 886-2-2792-7818	Eindhoven 31-40-267-7000	Warsaw 48-22-33-23-740/ 741	Milpitas, CA 1-408-519-3898

Worldwide Offices

Greater China

China	800-810-0345
Beijing	86-10-6298-4346
Shanghai	86-21-3632-1616
Shenzhen	86-755-8212-4222
Chengdu	86-28-8545-0198
Hong Kong	852-2720-5118

Taiwan	0800-777-111
Rueiguang	886-2-2792-7818
Yang Guang	886-2-2792-7818
Xindian	886-2-2218-4567
Taichung	886-4-2378-6250
Kaohsiung	886-7-229-3600

Asia Pacific

Japan	0800-500-1055
Tokyo	81-3-6802-1021
Osaka	81-6-6267-1887

Korea	080-363-9494
Seoul	82-2-3663-9494

Singapore	65-6442-1000
Singapore	65-6442-1000

Malaysia	1800-88-1809
Kuala Lumpur	60-3-7724-3555
Penang	60-4-397-3788
	60-4-397-4188

Indonesia	62-21-7690525
Jakarta	62-21-7690525

Thailand	66-2-248-3140
Bangkok	66-2-248-3140

India	1800-425-5071
Bangalore	91-80-2545-0206

Australia	1300-308-531
Melbourne	61-3-9797-0100
Sydney	61-2-9476-9300

Europe

Europe	00800-2426-8080
---------------	-----------------

Germany	49-89-12599-0
München	49-2103-97-885-0
Hilden	49-2103-97-885-0

France	33-1-4119-4666
Paris	33-1-4119-4666

Italy	39-02-9544-961
Milano	39-02-9544-961

Benelux & Nordics	31-76-5233-100
Breda	31-76-5233-100

UK	44-0118-929-4540
Reading	44-0118-929-4540

Poland	48-22-33-23-740/741
Warsaw	48-22-33-23-740/741

Russia	8-800-555-01-50
Moscow	7-495-232-1692

ADVANTECH

Enabling an Intelligent Planet

www.advantech.com

Please verify specifications before quoting. This guide is intended for reference purposes only. All product specifications are subject to change without notice. No part of this publication may be reproduced in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission of the publisher. All brand and product names are trademarks or registered trademarks of their respective companies. © Advantech Co., Ltd. 2012

ADVANTECH

Enabling an Intelligent Planet

Thin-Client Panel Computers

Next Generation of HMI –
The World's Most Intelligent Solution



2013

- Introduction
- Features & Functions
- Intelligent Software
- Selection Guide



Thin-Client Panel Computers

Nex Generation of HMI – The World’s Most Intelligent Solution

Advantech's new range of star products include several new models in the TPC (Touch Panel Computer), SPC (Stationary Panel Computer), FPM (Industrial Monitor) and WebOP (Operator Panel) range of devices, all of which come with 16:9 wide screen multi-touch displays; high-performance dual-core processors, and true flat front IP65 certified touch panels, making them more elegant and suitable for automotive production. Thin-client panel computers have combined cloud computing technology to make the solutions more efficient, reduce the cost of production and provide factory workers with more intuitive management of the production line.



16:9 Wide screen & Multi-touch

16:9 widescreen adds 40% viewing area to display more information for easier management than a traditional 4:3 display. By integrating multi-touch functionality, factory workers can increase operational safety with two-point key confirmation.



Magnesium-alloy Front

With a magnesium alloy front, the thin client panel computers have a reduced weight of 35% compared to aluminum alloy models with 18.5" and 21.5" sizes.



IP65 True Flat Touch Screen

Protected by IP65 certification with true flat PCT and resistive touch, thin-client panel computers support a 7H hardness anti-scratch surface to prevent accidental scratches caused by tools such as screwdrivers.



Intelligent Keys & Customized UI

Through touch-like intelligent-key support, thin-client panel computers provide an intuitive GUI & usability to simplify operating steps to save time. Customers can easily customize their own UI by using the updated SDK and API released on the official website.



Multi-color LED Indicator

With a multi-color LED indicator, factory workers can quickly realize the computer's operating status. The blue bar indicates the system is working while an orange bar shows that the system is in sleep mode.



Multiple I/Os with M12 Connector

The thin-client panel computers provide a wide variety of I/O ports including: COM-port, USB, 1000Base-T LAN, HDMI, and Audio ports with IP rating M12 connector.



More Powerful Graphical Processors

With a more powerful graphics processor, the thin-client panel computers offer advanced graphical performance for more efficiency when handling complicated processes.



Remote Management by Built-in Embedded Controller

With a built-in embedded controller combined with cloud computing technology, the thin-client panel computers provide a more efficient solution for remote management to reduce the TCO of production.



Supports Standard VESA Arm

With support for a standard 100x100mm VESA Arm, the thin-client panel computers are suitable for various applications such as automotive production.



Easy-Installation

With a special snap design, the thin-client panel computers can be easily installed by one person thereby speeding up the installation process.



Long Distance Display

By using the next generation digital video interface, the thin-client panel computers provide a long distance interface for video and USB signals.

Intelligent Software

SUSIAccess – Remote Device Management

SUSIAccess is an innovative remote device management and cloud-based software preloaded in all Advantech embedded solutions, allowing the efficient and centralized remote monitoring and management of embedded devices in real-time, device health status, system configuration, system protection, and recovery & backup. SUSIAccess targets the needs of creating a more intelligent and interconnected embedded computing solution.



- Remote Monitoring
- Remote On/Off, KVM
- System Recovery
- System Protection
- System Configuration
- Real-time Response

WebOP Designer – HMI/SCADA Software



WebOP Designer is proven in many application fields and is an easy-to-use integrated development tool featuring solution-oriented screen objects, high-end vector graphics, Microsoft Windows fonts for multi-language applications, recipes, alarms, data loggers and operation logging. It also includes online/offline simulation and other utility programs such as Data Transfer Helper (DTH); recipe editors and text editors. WebOP Designer Runtime which designed by WebOP Designer Software, and easy download into Embedded Operating System to support Microsoft Windows CE/XP/7 platforms.

- Shortcut & Execution Toolbar
- Icon Display Improves Work Efficiency
- Project Workspace
- An Intuitive Tree Display Makes Runtime Development Easy.
- Screen Design Worksheet
- Smart Screen Design
- Message Build List
- Compile & Simulate Results
- Draw Toolbar
- Object Toolbar
- Registered Components Display
- Edit Toolbar
- Dedicated Component Editing Screen
- Dialog Box