

Armagard Catalogue **2012**



Outdoor Digital Signage

www.Armagard.com





As enclosure specialists, Armagard provide cost effective solutions that minimise risk but maximize the display possibilities of an integrated screen.

With a background in hardware protection and over two decades of industry experience, Armagard enclosures fit a standard LCD screen and use a combination of durable outdoor protection and interior environmental control to sustain and support display efficiency.

Protecting against heavy rain, varying temperature levels and forceful impacts, Armagard enclosures are available for both indoor and outdoor applications, in both mounted and free standing designs.

Armagard continuously strive to change, innovate and deliver on the high expectations of our passionate customers.

Thank you... The Armagard Team

CONTENTS

Outdoor Enclosures		
Landscape	3	
Outdoor Totem/Digital Signage	4	
Portrait	5	
Stainless Landscape	6	
Double Landscape	7	
Indoor Enclosure		
Security Shield	8	
Retail Totem/Digital Signage	9	
Environmental Control	10	(
Dimension, Power & Weight	11	
Contact Numbers	12	

OUTDOOR ENCLOSURE

Call now on 0121-608-7210 to talk to one of our specialist advisors





THE PDS LANDSCAPE

A protective outdoor enclosure sealed to NEMA3/4 and durable against the effects of heavy rain, dust, extreme temperatures, high impact forces and electrical surges. LCD enclosures are available in sizes 24" up to 70" and are the perfect solution for outdoor locations or any area where vandalism may be a concern.

Available Sizes

19" 24" 32" 42" 46" 47" 52" 55" 60" 70"

(Other Sizes Available on Request)

Environmental Control



The Air Curtain ™



Internal Heating



Interior Mounting (Standard)



Dual Security Locks



Air Conditioning



Anti-Reflective



Toughened Windows



Closed Cell Insulation



Plenum Chambers



Suitable For

- Lobbies
- **Stations**
- **High Streets**
- ✓ Sports Clubs
- ✓ Industrial Parks



received my enclosures today - these are fantastic and just what I was looking for! I know my customer will be impressed with these, just as I am."

Thanks for the great service!

Stu Gray, Sound Ideas

ENCLOSURE OPTIONS	Base/Indoor	Outdoor Standard	Outdoor Cold Climate	
Product Code	PDS-(Size)-W-L-(T*)-B	PDS-(Size)-W-L-(T*)-S	PDS-(Size)-W-L-(T*)-H	
Temperature Range	(0°C to +30°C)	(-5°C to +35°C)	(-30°C to +35°C)	
NEMA Protection Rating	NEMA3	NEMA 4	NEMA4	
Window Type	Order Specific	Anti-Reflective Polycarbonate	Anti-Reflective Glass	
Universal Mounting Screen (Internal)	✓	✓	✓	
Dual Security Locks	✓	✓	✓	
Air Curtain ™ (Pat.Pend)		✓	✓	
Surge Protected Power	✓	✓	✓	
Exterior Plenum Chamber Cooling		✓	✓	
Internal Heater (Thermally Controlled)		✓	✓	
Filter Cooling System		✓	✓	
Closed Cell Insulation			✓	
PDS Mounts	Flat &	Tilt Mount (Purchased	l Separately)	

T* - Territory Specific











OUTDOOR DIGITAL SIGNAGE

Call now on +44 (0)121-608-7210 to talk to one of our specialist advisors





THE PDS OUTDOOR TOTEM

An aesthetic and presentable unit, the Outdoor Totem makes a great first impression. Environmentally controlled and sealed to NEMA3/4, the Outdoor Totem is a secure unit for digital signage requirements, driving advertising exposure and increasing customer engagement.

Available Sizes 46"/47"

(Other Sizes Available on Request)

Environmental Control



The Air Curtain ™



Internal Heating



Interior Mounting (Standard)



Dual Security Locks



Air Conditioning



Anti-Reflective



Toughened Windows



Closed Cell Insulation



Plenum Chambers





Cold Climate (H) Outdoor Model (Insulated)

Suitable For

- Doorways
- **Digital Adverts**
- ✓ Drive-Through's
- ✓ Window Displays
- ✓ Customer Service

FRICTION

"I must confess that the [plasma] cabinet is different from my expectations, and far exceeds them. I would like to express my gratitude to [Armagard] for producing an excellent product and in such a short time frame."

John Harrison, TMD

ENCLOSURE OPTIONS	Base/Indoor	Outdoor Standard	Outdoor Cold Climate	
Product Code	PDS-(Size)-TO-P-(T*)-B	PDS-(Size)-TO-P-(T*)-S	PDS-(Size)-TO-P-(T*)-H	
Temperature Range	(0°C to +30°C)	(-5°C to +35°C)	(-30°C to +35°C)	
NEMA Protection Rating	NEMA3	NEMA4	NEMA4	
Window Type	Order Specific	Anti-Reflective Polycarbonate	Anti-Reflective Glass	
Universal Mounting Screen (Internal)	✓	✓	✓	
Dual Security Locks	✓	✓	✓	
Air Curtain ™ (Pat.Pend)		✓	✓	
Surge Protected Power	✓	✓	✓	
Exterior Plenum Chamber Cooling		✓	✓	
Internal Heater (Thermally Controlled)		✓	✓	
Filter Cooling System		✓	✓	
Closed Cell Insulation			✓	
PDS Mount	Floor	Standing (Purchased S	Separately)	

T* - Territory Specific













OUTDOOR ENCLOSURE

Call now on +44 (0)121-608-7210 to talk to one of our specialist advisors





THE PDS PORTRAIT

Portrait enclosures can be better positioned at eye level and are ideal as information boards and digital advertising displays. Sealed to NEMA 3/4, enclosures can be fitted to handle temperatures between -30°C to +55°C (With Air-Conditioning) and offer a comprehensive solution for display security.

Available Sizes 42" 47" 52"

(Other Sizes Available on Request)

Environmental Control



The Air Curtain ™



Internal Heating



Interior Mounting (Standard)



Dual Security Locks



Air Conditioning



Anti-Reflective



Toughened Windows



Closed Cell Insulation



Plenum Chambers



Standard (S) Outdoor Model

Suitable For

- Studios
- Receptions
- Store Fronts
- **Transport Areas**
- Information Displays

faurecia

Technical perfection, automotive passi

"We use the LCD housing in our factory in Grojec, it's ideally suited to our needs, the device works perfectly and is recommendable."

Wojciech Benerat, Faurecia

ENCLOSURE OPTIONS	TIONS Base/Indoor Outdoor Standard		Outdoor Cold Climate
Product Code	PDS-(Size)-W-P-(T*)-B	PDS-(Size)-W-P-(T*)-S	PDS-(Size)-W-P-(T*)-H
Temperature Range	(0°C to +30°C)	(-5°C to +35°C)	(-30°C to +35°C)
NEMA Protection Rating	NEMA3	NEMA4	NEMA4
Window Type	Order Specific	Anti-Reflective Polycarbonate	Anti-Reflective Glass
Universal Mounting Screen (Internal)	✓	✓	✓
Dual Security Locks	✓	✓	✓
Air Curtain ™ (Pat.Pend)		✓	✓
Surge Protected Power	✓	✓	✓
Exterior Plenum Chamber Cooling		✓	✓
Internal Heater (Thermally Controlled)		✓	✓
Filter Cooling System		✓	✓
Closed Cell Insulation			✓
PDS Mounts	Flat &	Tilt Mount (Purchased	l Separately)

T* - Territory Specific















THE SDS STAINLESS LANDSCAPE

aesthetic and presentable unit, stainless enclosures are manufactured from 316 (food grade) steel, perfect for hygiene and food preparation environments that are washed down daily.

Available Sizes 24" 42"

(Other Sizes Available on Request)

Environmental Control



The Air Curtain ™



Internal Heating



Interior Mounting (Standard)



Dual Security Locks



Air Conditioning



Anti-Reflective



Toughened Windows



Closed Cell Insulation



Plenum Chambers



Standard (S) Outdoor Model

Suitable For

- ✓ Food Manufacture
- **Medical Applications**
- Laboratories
- **Design Features**
- **Medical Areas**



"It's been 2 years since we started working with Armagard and I'm more than satisfied with the quality of the equipment and by the quality of support and advice received."

Michel Kremer, Patissserie

ENCLOSURE OPTIONS	Base/Indoor	Outdoor	Outdoor	
		Standard	Cold Climate	
Product Code	SDS-(Size)-W-L-(T*)-B	SDS-(Size)-W-L-(T*)-S	SDS-(Size)-W-L-(T*)-H	
Temperature Range	(0°C to +30°C)	(-5°C to +35°C)	(-30°C to +35°C)	
NEMA Protection Rating	NEMA3	NEMA4	NEMA4	
Window Type	Order Specific	Anti-Reflective Polycarbonate	Anti-Reflective Glass	
Universal Mounting Screen (Internal)	✓	✓	✓	
Dual Security Locks	✓	✓	✓	
Air Curtain ™ (Pat.Pend)		✓	✓	
Surge Protected Power	✓	✓	✓	
Exterior Plenum Chamber Cooling	✓	✓	✓	
Internal Heater (Thermally Controlled)		✓	✓	
Filter Cooling System		✓	✓	
Closed Cell Insulation			✓	
PDS Mounts	Flat &	Tilt Mount (Purchased	l Separately)	

T* - Territory Specific





DOUBLE OUTDOOR ENCLOSURE

Call now on +44 (0)121-608-7210 to talk to one of our specialist advisors





THE PDS DOUBLE LANDSCAPE

A new enclosure to the Armagard line featuring a grey finish, the dual facing enclosure separates display information making stacked information easier to read and great for environments with limited space.

Available Sizes 19"

(Other Sizes Available on Request)

Environmental Control



The Air Curtain ™



Internal Heating



Interior Mounting (Standard)



Dual Security Locks



Air Conditioning



Anti-Reflective



Toughened Windows



Closed Cell Insulation



Plenum Chambers



Suitable For

- Lobbies
- Stations
- **High Streets**
- Sports Clubs
- Industrial Parks

AGC

"We've installed the enclosures and are happy with the installation and quality of the product, which is both robust and practical".

David Delavallée, AGC

ENCLOSURE OPTIONS	Base/Indoor	Outdoor Standard	Outdoor Cold Climate	
Product Code	PDS-(Size)-WD-L-(T*)-B	PDS-(Size)-WD-L-(T*)-S	PDS-(Size)-WD-L-(T*)-H	
Temperature Range	(0°C to +30°C)	(-5°C to +35°C)	(-30°C to +35°C)	
NEMA Protection Rating	NEMA3	NEMA 4	NEMA4	
Window Type	Order Specific	Anti-Reflective Polycarbonate	Anti-Reflective Glass	
Universal Mounting Screen (Internal)	✓	✓	✓	
Dual Security Locks	✓	✓	✓	
Air Curtain ™ (Pat.Pend)		✓	✓	
Surge Protected Power	✓	✓	✓	
Exterior Plenum Chamber Cooling		✓	✓	
Internal Heater (Thermally Controlled)		✓	✓	
Filter Cooling System		✓	✓	
Closed Cell Insulation			✓	
PDS Mounts	Flat &	Tilt Mount (Purchased	l Separately)	

T* - Territory Specific













INDOOR ENCLOSURE

Call now on +44 (0)121-608-7210 to talk to one of our specialist advisors





THE PSS SECURITY SHIELD

The Security Shield 42" is an LCD enclosure fitted over a pre-existing display, which protects against velocity forces and vandal Manufactured from powder coated steel and equipped with a high impact polycarbonate window (20x stronger than glass), the security shield is fitted with two key locks and is a great cost efficient unit for areas with lots of daily activity.

Available Sizes 42"

(Other Sizes Available on Request)

Enclosure Control



Rubber Seals



Dust Vents



Toughened Windows



Dual Security Locks





Suitable For

- ✓ Schools
- ✓ Sports Clubs
- ✓ Youth Facilities
- **Transport Areas**
- ✓ Community Centres



"Armagard offered an effective solution to our problem. Mixing speed and efficiency, Armagard has responded perfectly to our needs."

Benjamin Launay, Vétigraph

ENCLOSURE OPTIONS	Base/Indoor		
Product Code	PSS-(Size)-W-L-B		
Temperature Range	(0°C to +30°C)		
NEMA Protection Rating	NEMA1		
Window Type	Polycarbonate		
Universal Mounting Screen (Internal)	✓		
Dual Security Locks	✓		
Dust Vents	✓		
Rubber Seals	✓		
Anti Reflective	(Optional)		
PSS Mount	Wall Mounted		
Optional Anti-Reflective Window			



INDOOR DIGITAL SIGNAGE

Call now on +44 (0)121-608-7210 to talk to one of our specialist advisors





THE IDS RETAIL TOTEM

Floor standing and available for a screen sizes 32", 42" & 46", the Retail Totem utilises moving and static images with an integrated LCD screen and removable front and back panels that maximize the advertising potential of your business for point-of-sale areas.

Available Sizes 32" 42" 46"

(Other Sizes Available on Request)



Interchangeable Front & Back Panels

Personalised Artwork Designs

Light Weight & Quick Setup

Increase Dwelling & Visitation







Media Ready (MR) Indoor Model

Suitable For

- ✓ Events
- Exhibitions
- ✓ Retail Stores
- Shop Floors
- ✓ In-Store Advertising

"The quality of the cabinets is what makes our customers really happy. They know that there are cheaper products on the market but with Armagard you know what you are going to get and the high quality is the main thing that attracts people."

Thomas Ottoman, Norex

ENCLOSURE OPTIONS	Base Indoor	Printed Indoor	Media Ready Indoor		
Product Code	IDS-(Size)-TR-P-B	IDS-(Size)-TR-P-P	IDS-(Size)-TR-P-MR		
Temperature Range	(0°C to +30°C)	(0°C to +30°C)	(0°C to +30°C)		
Window Type	Polycarbonate	Polycarbonate	Polycarbonate		
Aluminum Supports	✓	✓	✓		
Base Plate	✓	✓	✓		
Plain Boards	✓				
Printed Boards		✓	✓		
LCD Screen		✓	✓		
Media Player			✓		
Surge Protection	Territory Specific				
IDS Mount	Floor Standing				
	Optional Anti-Re	flective Window			










ENVIRONMENTAL CONTROL

Protecting hardware in several types of environments, Armagard Environmental Control creates a monitored interior system using key components that regulate and control electrical hardware from external threats, such as extreme weather and overheating.









Interior Mounting Brackets | Reducing twisting and distributing weight evenly, Armagard bracket arms can be moved independently forward or backwards, allowing installers to optimise their display for the best possible viewing angle.



Dual Security Locks Fitted with two key security locks, locking bar and anti-torsion bolts, Armagard placement security offers piece-of-mind for units left in unmanned locations.



Plenum Chambers Allows the enclosure to be fully jet washed while allowing a filtered air-flow to transfer heat away, Plenum Chambers prevent any water from entering the unit and damaging the display.



Air Curtain TM Directing a constant flow of air across an installed display, the Armagard Air-Curtain reduces damage from heat build-up, direct sunlight and freezing conditions, optimising window clarity, promotion efficiency and increasing display lifespan.



Internal Heater | Stops your screen from freezing over in winter, Internal Heaters maintain the optimum level of warmth within the enclosure, increasing the average air temperature to sustain display longevity.



Closed Cell Insulation | Improving thermal performance, Armagard's 25mm low temperature insulation eliminates any thermal bridges and improves energy efficiency throughout the enclosure.



Fan Support A standard component on all enclosures, fan support provides vital air circulation around an enclosure, preventing dust from settling, one of the main causes of overheating.



Air Conditioning | for areas that reach extreme temperatures, air-conditioning provides support for heated environments of up to 55°C.



Automatic Thermostats | Programmed on/off support for air-fans, heating and emergency display shut-down in extreme temperatures.



Toughened Windows | Available in glass or polycarbonate, Armagard toughened windows carry unique high-strength properties, making them ideal for busy or vandal prone areas.



Anti-Reflective | Available in either glass or polycarbonate, anti-reflective windows reduce glare and surrounding light reflections, presenting a clear and accurate image when in direct sunlight. (Note: Glare can never be fully removed, to reduce glare to its lowest level, we recommend an anti-reflective glass with a 1% reflection rating, over a polycarbonate of 8%).



Dimensions, Power & Weight

Model	Height (mm)	Width (mm)	Depth (mm)	Window Height (mm)	Window Width (mm)	Power*	Weight*
Landscape							
PDS-24-W-L-UK	523	721	212.5	343	561	33w	25-30kg
PDS-32-W-L-UK	630	895	232.8	450	735	34w	30-35kg
PDS-42-W-L-UK	761	1127	232.8	536	970	64w	35-40kg
PDS-46-W-L-UK	835	1300	232.2	584	1030	135w	40-45kg
PDS-47-W-L-UK	815	1230	232.2	591	1046	135w	40-45kg
PDS-52-W-L-UK	936	1351	232.8	706	1191	65w	45-50kg
PDS-55-W-L-UK	980	1430	232.5	730	1258	69w	50-55kg
PDS-60-W-L-UK	1050	1530	232.4	807	1370	74w	60-70kg
PDS-70-W-L-UK	1192.2	1800	264.6	922	1589	98w	80-90kg
Security Shield							
PSS-42-W-L-UK	760	1130	160	563	970	N/A	10-15kg
Portrait							
PDS-42-W-P-UK	1305	725	232.2	970	563	64w	35-40kg
PDS-47-W-P-UK	1400	750	232.2	1046	591.2	135w	40-45kg
PDS-52-W-P-UK	1520	870	232.2	1191	706	65w	45-50kg
Totem							
PDS-47-TO-P-UK	1828	750	231.9	1046	591.2	135w	45-50kg
Retail Totem							
42"	2006	855	179.81	TBC	TBC	N/A	TBC
The dimensions used for	The dimensions used for the 42" Retail Totem can also be used for the 46"						

Power* Power consumption will vary between different enclosure modelsWeight* Overall weight will vary between different enclosure models





PHONE - (International +33) 0826-805-680

EMAIL – mireille.godefroy@armagard.com



PHONE – (International +39) 06.657487381 EMAIL – mara.fontana@armagard.com



PHONE - (International +34) 911-819-768 EMAIL – cecilia.chavez@armagard.com



PHONE – (International +49) 02821-777-6-2804 EMAIL – lena.sperber@armagard.com



PHONE – (International +48) 022-526-6149 EMAIL – agnieszka.gorniak@armagard.com



PHONE – (International +44) 0121-608-7226 EMAIL – parab@armagard.com



PHONE – (International +001) 1-866-434-0807 EMAIL – mark.thomas@armagard.com

Some of Our Customers...





























Armagard Ltd | Fortnum Close | Kitts Green | Birmingham | B33 0LG | United Kingdom

Call: +44 (0)121-608-7210